



# ST518 All-Position

The ST518 is a durable, all-position tire for mixed service use.

## FEATURES & BENEFITS

- Sumitomo four steel belt casing construction resists punctures, increases vehicle stability and contributes to more retread cycles.
- Application-specific tread compound resists cutting and chipping.



Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Tread Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5531116*	10.00R20	146/143K	H/16	7.50	7.00	6,610	6,005	120	41.5	11.0	12.5	20	19.5	502	68
5531120*	11.00R20	150/147K	H/16	8.00	7.50	7,390	6,780	120	42.8	11.7	13.2	21	19.9	488	68
5531155	12R22.5	150/147K	H/16	9.00	8.25	7,390	6,780	120	42.8	12.0	13.5	21	20.0	488	68

\* Includes tube and flap

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.



# SUMITOMO TIRES

*For what drives you.*

sumitomotrucktires.com • treadxpress.com • 1-866-822-4968