



# ST709 SE Regional Steer

The ST709 SE is a regional steer tire that's durable enough when there's serious work to be done, but versatile enough to display on-highway manners.

## FEATURES & BENEFITS

- Beefy 20/32" tread depth applied to a wide, flat casing for much longer life in high-scuff applications.
- Chevron block center ribs with lateral sipes effectively cut water on wet roads for enhanced traction and safety.
- Thick curbing ribs help shield casing from sidewall damage.
- Stone ejectors protect the casing from damage in the base of the tread groove.
- An innovative design helps control irregular wear during on-highway use.
- Built with SmartWay Verified technology.




This company manufactures:

- EPA SmartWay verified technologies
- Verified equipment for SmartWay Certified Tractors and/or
- Verified equipment for SmartWay Certified Trailers

As a result, we assist SmartWay partners with meeting their goals of energy efficiency and emissions reductions.

Learn more about...  
**SmartWay**  
[www.epa.gov/smartway](http://www.epa.gov/smartway)



Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Tread Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5532952	11R22.5	146/143L	H/16	8.25	7.50	6,610	6,005	120	41.5	11.1	12.5	20	19.4	500	75
5532959	11R24.5	149/146L	H/16	8.25	7.50	7,160	6,610	120	43.5	11.1	12.5	20	20.4	477	75
5532975	295/75R22.5	144/141L	G/14	9.00	8.25	6,175	5,675	110	40.2	11.3	13.2	20	18.8	517	75
5532978	285/75R24.5	144/141L	G/14	8.25	7.50	6,175	5,675	110	41.6	10.6	12.5	20	19.5	500	75

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.



# SUMITOMO TIRES

For what drives you.

sumitomotrucktires.com • treadxpress.com • 1-866-822-4968