



ST908 Open Shoulder Drive

The ST908 open shoulder drive tire has an excellent reputation among fleets.

FEATURES & BENEFITS

- A continuous center rib delivers long life and highway stability, while shoulder lugs bite for excellent traction on soft surfaces.
- 26/32" tread depth promotes long life and year round service.
- Four steel belt casing construction resists punctures, increases vehicle stability, and contributes to more retread cycles.



Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Tread Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5531217*	10.00R20	146/143K	H/16	7.50	7.00	6,610	6,005	120	41.8	10.9	12.5	26	19.5	498	68
5531252	11R22.5	146/144L	H/16	8.25	7.50	6,610	6,005	120	41.9	10.9	12.6	26	19.6	495	75
5531263	315/80R22.5	154/151M	J/18	9.00	9.00	8,270	7,610	120	42.8	12.3	13.8	25	19.8	486	81
5531275	295/75R22.5	144/141L	G/14	9.00	8.25	6,175	5,675	110	40.7	10.7	13.2	26	19.0	512	75
5531287	255/70R22.5	140/137M	H/16	7.50	6.75	5,510	5,070	120	36.9	9.9	11.3	25	17.2	578	81

* Includes tube and flap

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.



SUMITOMO TIRES

For what drives you.

sumitomotrucktires.com • treadxpress.com • 1-866-822-4968