

TOWMAX STR^{II} PREMIUM ST RADIAL

ARTICLE NO.	TIRE SIZE	LR/PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH (32NDS)	TYPE	RIM WIDTH (INCH)	OVERALL DIAMETER	SECTION WIDTH (INCH)	WGT (LBS)	MAX. RATED LOAD @ PSI SINGLE
MAX13T	ST175/80R13	C/6	91/87	L	9	TL	5.00	24.0	6.9	16	1360 @ 50
MAX15T	ST185/80R13	C/6	94/89	L	9	TL	5.00	24.7	7.3	17	1480 @ 50
MAX36T	ST205/75R14	C/6	100/96	L	10	TL	5.50	26.1	7.7	20	1760 @ 50
MAX37T	ST205/75R14	D/8	105/101	L	10	TL	5.50	26.1	7.7	21	2040 @ 65
MAX38T	ST215/75R14	C/6	102/98	L	10	TL	6.00	26.7	8.4	22	1870 @ 50
MAX48T	ST205/75R15	C/6	101/97	L	10	TL	5.50	27.1	7.7	22	1820 @ 50
MAX49T	ST205/75R15	D/8	107/102	L	10	TL	5.50	27.1	7.8	23	2150 @ 65
MAX51T	ST225/75R15	D/8	113/108	L	10	TL	6.00	28.3	8.8	28	2540 @ 65
MAX53T	ST225/75R15	E/10	117/112	L	10	TL	6.00	28.3	8.8	29	2860 @ 80
MAX24T	ST235/80R16	E/10	124/120	L	10	TL	6.50	30.7	9.2	34	3520 @ 80
MAX25T	ST235/80R16	F/12	127/122	L	10	TL	6.50	30.7	9.2	37	3860 @ 100
MAX17T	ST235/85R16	E/10	125/122	L	10	TL	6.50	31.7	9.2	36	3640 @ 80
MAX18T	ST235/85R16	F/12	128/124	L	10	TL	6.50	31.7	9.2	37	3960 @ 95

Nylon Overlay on 15" and 16" sizes

The **TOWMAX STR^{II}** is our next generation and most advanced ST radial, designed and built to provide you and your customers with exceptional performance and warranty support. This tire has been designed and built with the most advanced technology and manufacturing processes to provide superior resistance to heat build-up and a more energy efficient tread compound.

Features & Benefits

- Optimized tread compound for improved rolling resistance
- Computer-designed tire profile to improve resistance to heat build-up
- Nylon overlays on 15" & 16" sizes for superior strength and durability
- 2-year Nationwide Roadside Assistance Program

Applications:

- 5th Wheel, RV, and Utility Trailers

