

ENCOUNTER AT



ALL-TERRAIN SUV/LT

Discover the new standard of all-season drivability and all-terrain durability with the Sumitomo Encounter AT ... the go-anywhere, do-anything all-terrain light truck tire for CUVs, SUVs and Pickups.

FEATURES & BENEFITS

- Exceptional traction in mud and heavy snow provides control in harsh weather and on tough terrain for true all-surface performance year round
- Optimized tread design reduces road noise and delivers smooth, comfortable on-highway performance
- Designed from the inside out to provide versatile on-road drivability and off-road strength
- All sizes rated with the U.S. Tire Manufacturers Association's 3-Peak Mountain Snowflake symbol for severe snow performance
- Advanced tread technology is built to last and backed by a 60,000-mile treadwear warranty
- Backed by a best-in-class warranty protection package for consumer confidence and peace of mind



Non-Directional, 5-Rib Tread Design optimizes ride stability and protects against irregular wear

Optimized Tread Pattern stabilizes handling and steering response for a smooth, quiet ride

Deep Circumferential Grooves boost wet grip performance and provides superior wear life

Variable-Width Shoulder Lugs evacuate rocks, sand and other debris for superior off-road grip

3D Wave Sipes enhance traction and performance in snow, mud and other soft surfaces

Severe Snow Certification ensures reliable winter performance in heavy snow

FITS

CUVs, SUVs, pickups and vans, including later model fitments

SIZES

Available in 16" - 20" Metric and LT sizes

WARRANTY

60,000-Mile / 100,000-KM Treadwear for Metric and LT Sizes

2-Year, 24/7 Tire Roadside Assistance

30-Day Test Drive

1-Year Tire Road Hazard Protection Plan

Lifetime Replacement for Workmanship and Material Defects

OFF-ROAD TRACTION 10

TREAD LIFE 9

RIDE COMFORT 8

SNOW AND ICE TRACTION 10

WET PERFORMANCE HANDLING 9

ENCOUNTER AT



ALL-TERRAIN SUV/LT

Product Code	Tire Size	Load Range	Service Desc.	UTQG	Measuring Rim Width (in)	Approved Rim Width		Maximum		Dual Maximum		Overall Diameter (in)	Section Width (in)	Tread Width (in)	Static Loaded Radius (in)	Revs. Per. Mile	Tread Depth	Ship Weight (lbs)
						Min. (in)	Max. (in)	Air (lbs psi)	Load (lbs)	Air (lbs psi)	Load (lbs)							
ATH64	235/75R15	SL	105T	660 A B	6.5	6.0	8.0	51	2039	-	-	29.0	9.3	7.4	12.9	729	13	34.6
ATH66	235/75R15	XL	109T	660 A B	6.5	6.0	8.0	50	2271	-	-	29.0	9.3	7.4	12.9	729	13	34.6
ATH79	245/75R16	SL	111T	660 A B	7.0	6.5	8.0	51	2403	-	-	30.5	9.8	7.7	13.6	694	13	39.1
ATH81	265/75R16	SL	116T	660 A B	7.5	7.0	9.0	51	2756	-	-	31.7	10.7	8.3	14.1	669	13	44.5
ATH53	235/70R16	SL	106T	660 A B	7.0	6.0	8.0	51	2094	-	-	29.0	9.5	7.8	13.0	729	13	36.5
ATH80	245/70R16	SL	107T	660 A B	7.0	6.5	8.0	51	2149	-	-	29.6	10.0	8.1	13.2	714	13	39.9
ATH86	255/70R16	SL	111T	660 A B	7.5	6.5	8.5	51	2403	-	-	30.2	10.2	8.5	13.5	701	13	39.5
ATH93	265/70R16	SL	112T	660 A B	8.0	7.0	9.0	51	2469	-	-	30.7	10.9	8.8	13.7	689	14	43.3
ATH45	235/75R17	SL	109T	660 A B	6.5	6.0	8.0	51	2271	-	-	31.3	9.4	7.4	14.0	674	13	38.8
ATH09	P235/70R17	XL	108T	660 A B	7.0	6.0	8.0	50	2205	-	-	30.1	9.5	7.8	13.5	700	13	38.1
ATH89	245/70R17	SL	110T	660 A B	7.0	6.5	8.0	51	2337	-	-	30.7	10.0	8.1	13.7	689	13	41.4
ATH10	255/70R17	SL	112T	660 A B	7.5	6.5	8.5	51	2469	-	-	31.1	10.3	8.5	13.9	679	13	42.0
ATH87	265/70R17	SL	115T	660 A B	8.0	7.0	9.0	51	2679	-	-	31.7	10.9	8.8	14.2	666	14	45.6
ATH83	P285/70R17	SL	117T	660 A B	8.5	7.5	9.5	51	2833	-	-	32.9	11.7	9.4	14.6	645	14	50.0
ATH55	245/65R17	SL	107T	660 A B	7.0	7.0	8.5	51	2149	-	-	29.6	9.7	8.3	13.3	719	13	38.7
ATH20	255/65R17	SL	110T	660 A B	7.5	7.0	9.0	51	2337	-	-	30.1	10.3	8.6	13.5	707	13	41.0
ATH58	265/65R17	SL	112T	660 A B	8.0	7.5	9.5	51	2469	-	-	30.6	10.7	8.9	13.7	697	13	42.8
ATH52	255/70R18	SL	113T	660 A B	7.5	6.5	8.5	51	2535	-	-	32.2	10.3	8.5	14.5	654	13	44.8
ATH22	265/70R18	SL	116T	660 A B	8.0	7.0	9.0	51	2756	-	-	32.8	10.8	8.8	14.7	644	14	46.6
ATH56	265/65R18	SL	114T	660 A B	8.0	7.5	9.5	51	2601	-	-	31.5	10.7	8.9	14.1	675	13	46.1
ATH63	275/65R18	SL	116T	660 A B	8.0	7.5	9.5	51	2756	-	-	32.1	10.9	9.3	14.4	662	14	47.9
ATH91	265/60R18	SL	110T	660 A B	8.0	7.5	9.5	51	2337	-	-	30.6	10.6	8.9	13.8	694	13	43.3
ATH15	275/60R20	SL	115T	660 A B	80	7.5	9.5	51	2679	-	-	33.0	10.9	9.3	15.0	640	13	48.4
ATH73	275/55R20	XL	117T	660 A B	8.5	7.5	9.5	50	2833	-	-	31.9	11.0	9.4	14.5	661	13	48.6
ATH17	LT235/85R16	E	120/116R	-	6.5	6.0	7.5	80	3042	80	2778	31.7	9.5	7.2	14.6	658	17	47.4
ATH26	LT225/75R16	E	115/112R	-	6.0	6.0	7.0	80	2680	80	2470	29.3	8.7	7.1	13.5	713	17	41.4
ATH38	LT245/75R16	E	120/116R	-	7.0	6.5	8.0	80	3042	80	2778	30.3	9.8	7.7	14.0	688	17	48.3
ATH39	LT265/75R16	E	123/120R	-	7.5	7.0	8.0	80	3415	80	3085	31.5	10.6	8.3	14.5	664	18	54.5
ATH67	LT285/75R16	E	126/123R	-	8.0	7.5	9.0	80	3750	80	3415	32.7	11.5	8.9	15.0	640	18	61.0
ATH95	LT235/80R17	E	120/117R	-	6.5	6.0	7.5	80	3085	80	2835	31.8	9.3	7.1	14.7	655	17	47.9
ATH19	LT245/75R17	E	121/118R	-	7.0	6.5	7.5	80	3195	80	2910	31.7	9.7	7.7	14.6	659	17	49.7
ATH70	LT245/70R17	E	119/116S	-	7.0	6.5	8.0	80	3000	80	2755	30.7	10.0	8.1	14.3	676	17	48.3
ATH92	LT265/70R17	E	121/118S	-	8.0	7.0	8.5	80	3195	80	2910	31.9	10.9	8.8	14.8	653	18	52.8
ATH84	LT285/70R17	E	121/118S	-	8.5	7.5	9.0	80	3195	80	2910	32.8	12.0	9.4	15.1	637	18	58.5
ATH02	LT315/70R17	E	121/118S	-	9.5	8.0	11.0	65	3195	65	2910	34.6	13.1	10.2	15.9	604	20	72.8
ATH30	LT265/70R18	E	124/121S	-	8.0	7.0	9.0	80	3525	80	3195	32.8	11.1	8.8	15.2	634	18	59.5
ATH72	LT275/70R18	E	125/122S	-	8.0	7.0	8.5	80	3640	80	3305	33.4	11.2	9.1	15.5	624	18	60.6
ATH74	LT275/65R18	E	123/120S	-	8.0	7.5	9.0	80	3415	80	3085	32.1	10.9	9.2	14.8	651	18	59.5
ATH57	LT285/65R18	E	125/122S	-	8.5	8.0	10.0	80	3640	80	3305	32.5	11.5	9.6	15.0	644	18	64.2
ATH98	LT325/65R18	E	127/124R	-	9.5	9.0	12.0	65	3860	65	3525	34.7	13.3	10.9	15.9	604	20	76.7
ATH43	LT275/65R20	E	126/123S	-	8.0	7.5	9.5	80	3750	80	3415	34.2	10.9	9.3	15.9	611	18	64.6
ATH75	LT265/60R20	E	121/118R	-	8.0	7.5	9.5	80	3195	80	2910	32.7	10.3	8.8	15.3	636	18	58.2
ATH88	LT285/60R20	E	125/122R	-	8.5	8.0	10.0	80	3640	80	3305	33.5	11.5	9.4	15.6	622	18	61.5
ATH99	LT325/60R20	D	121/118S	-	9.5	9.0	12.0	50	3195	50	2910	35.4	13.0	11.1	16.4	589	20	83.8
ATH90	LT285/55R20	E	122/119R	-	9.0	8.0	10.0	80	3305	80	3000	32.5	11.4	9.8	15.1	640	18	58.2
ATH54	LT305/55R20	E	121/118S	-	9.5	8.5	11.0	65	3195	65	2910	33.1	12.4	10.5	15.4	628	19	68.2
ATH44	31X10.50R15LT	C	109R	-	8.5	7.0	9.0	50	2270	-	-	30.4	10.9	8.3	13.9	697	18	48.5
ATH71	35X12.50R20LT	E	121Q	-	10.0	8.5	11.0	65	3195	-	-	34.7	13.0	10.8	16.2	604	20	76.3