

TOURING LS T/H/V & TOURING LX

Touring All-Season



Touring All-Season

Upgrade your drive! Get traction and performance you can count on regardless of the weather with the Sumitomo Touring LS T/H/V and Touring LX. With a smooth ride, minimal road noise and extended tread life, this tire provides it all.

- 1 Improved handling quality to take the higher speed ratings of today's high performance luxury sedans, touring vehicles, SUV's and crossovers
- 2 Next-generation, advanced carbon tread compound for enhanced all-season performance, wet traction and tread life
- 3 Innovative shoulder blocks provide superior cornering traction and security
- 4 Four circumferential tread grooves allow exceptional water drainage to resist hydroplaning
- 5 Enhanced sidewall stiffness for improved cornering



Superior Warranty Package for Maximum Security and Confidence

- 65,000-Mile Limited Treadwear Warranty for T-rated LS
- 55,000-Mile Limited Treadwear Warranty for H & V-rated LS
- 50,000-Mile Limited Treadwear Warranty for T/H/V-rated LX
- 100% Replacement for Workmanship and Material Defects
- 2-Year, 24/7 Tire Roadside Assistance

Constructed for Premium Performance

- Stronger, wider steelbelts maximize durability
- Touring profile improves overall performance and tread life
- Strong polyester cord body for structural rigidity



- Enhanced rubber compounds resist wear
- Computer-designed tread offers enhanced comfort and a quieter ride

TOURING LS T/H/V								UTQG 520 A B (TR) , 460 A A (HR/VR)						
Product Code	Tire Size	Service Description	Measuring Rim Width (in)	Approved Rim Width		Maximum		Overall Diameter (in)	Section Width (in)	Tread Width (in)	Static Loaded Radius (in)	Revs. Per. Mile	Tread Depth	Ship Weight (lbs)
				Min. (in)	Max. (in)	Air (lbs psi)	Load (lbs)							
STT29U	205/70R15	96T	6.0	5.0	7.0	44	1,565	26.5	8.1	6.1	11.9	795	11	23.4
STT31U	215/70R15	98T	6.5	5.5	7.0	44	1,653	27.0	8.9	6.5	12.1	781	12	24.7
STT27U	185/65R15	88T	5.5	5.0	6.5	44	1,235	24.7	7.3	5.7	11.2	856	11	17.6
STT28U	195/65R15	91T	6.0	5.5	7.0	44	1,356	25.1	7.7	6.1	11.3	845	11	19.0
STT44U	205/65R15	94T	6.0	5.5	7.5	44	1,477	25.7	8.2	6.4	11.6	826	11	20.9
STT73U	185/60R15	84T	5.5	5.0	6.5	44	1,102	24.0	7.1	5.7	10.9	880	11	17.4
STT41U	195/60R15	88T	6.0	5.5	7.0	44	1,235	24.2	7.4	6.4	11.0	874	11	18.1
STT55U	215/65R16	98T	6.5	6.0	7.5	44	1,653	27.1	8.5	6.7	12.2	783	11	24.5
STT48U	215/60R16	95T	6.5	6.0	7.5	44	1,521	26.2	8.3	7.0	11.9	805	12	24.5
STT52U	225/60R16	98T	6.5	6.0	8.0	44	1,653	26.6	8.7	7.3	12.0	798	11	25.6
STT42U	205/55R16	91T	6.5	5.5	7.5	44	1,356	25.1	8.1	6.9	11.5	840	11	22.9
STT97U	215/65R17	99T	6.5	6.0	7.5	44	1,709	28.3	8.6	6.7	12.8	749	11	26.9
STH76U	225/65R17	102H	6.5	6.0	8.0	51	1,874	28.6	9.0	7.0	12.9	740	12	29.1
STH77U	235/65R17	104H	7.0	6.5	8.5	51	1,984	29.2	9.6	7.3	13.1	727	12	31.3
STT95U	215/60R17	96T	6.5	6.0	7.5	44	1,565	27.2	8.5	7.0	12.4	776	12	25.8
STT96U	225/60R17	99T	6.5	6.0	8.0	44	1,709	27.8	8.7	7.3	12.6	762	12	24.9
STT88U	225/55R17	97T	7.0	6.0	8.0	44	1,609	26.8	8.7	7.3	12.2	786	11	24.7
STH01U	225/55R18	98H	7.0	6.0	8.0	51	1,653	27.8	8.9	7.6	12.7	758	11	26.7
STV03U	235/55R18	100V	7.5	6.5	8.5	51	1,784	28.2	9.4	7.9	12.9	742	12	28.2
5515910††	P175/70R13	82T	5.0	4.5	6.0	51	1,036	22.7	6.7	5.2	10.2	927	9	15.0
5515928U†	P215/70R14	96T	6.5	5.5	7.0	51	1,554	25.9	8.5	6.5	11.6	815	10	20.0
5515940††	P175/65R14	81T	5.0	5.0	6.0	51	1,019	23.0	6.7	5.4	10.4	919	10	15.0

† Size is offered as Sumitomo HTR T4, featuring same tread design

†† Size is offered as Sumitomo HTR T4, featuring same tread design with UTQG of 560 A B

TOURING LX								UTQG 520 A B (TR) , 460 A A (HR/VR)						
Product Code	Tire Size	Service Description	Measuring Rim Width (in)	Approved Rim Width		Maximum		Overall Diameter (in)	Section Width (in)	Tread Width (in)	Static Loaded Radius (in)	Revs. Per. Mile	Tread Depth	Ship Weight (lbs.)
				Min. (in)	Max. (in)	Air (lbs psi)	Load (lbs)							
STL08U	235/60R17	102T	7.0	6.5	8.5	44	1,874	28.2	9.4	7.7	12.8	751	11	30.8
STT88U	225/55R17	97T	7.0	6.0	8.0	44	1,609	26.8	8.7	7.3	12.2	786	11	24.7
STL49U	235/60R18	103H	7.0	6.5	8.5	51	1,929	29.2	9.4	7.7	13.2	725	11	32.8
STL68U	245/60R18	105T	7.0	7.0	8.5	44	2,039	29.7	9.8	8.0	13.4	713	11	31.7
STL91U	265/60R18	110T	8.0	7.5	9.5	44	2,337	30.6	10.7	8.7	13.8	694	12	36.3
STL36U	255/55R18	105V	8.0	7.0	9.0	51	2,039	29.1	10.4	8.8	13.2	725	12	34.8
STL36U	255/55R18	105V	8.0	7.0	9.0	51	2,039	29.1	10.4	8.8	13.2	725	12	34.8